

## HEO Specifications

Model No.	PSI	GPM	HP/Motor	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HEO-2004-0E2G	2000	4.2	6.0/230V, 1Ø, 27.1A	386,400	56.5in.x29in.x49.75in.	844 lbs.	724 lbs.
HEO-2004-0E3G	2000	4.2	6.0/230V, 3Ø, 17.6A	386,400	56.5in.x29in.x49.75in.	844 lbs.	724 lbs.
HEO-2004-0E4G	2000	4.2	6.0/460V, 3Ø, 8.8A	386,400	56.5in.x29in.x49.75in.	844 lbs.	724 lbs.
HEO-2004-0E8G	2000	4.2	6.0/208V, 1Ø, 29.8A	386,400	56.5in.x29in.x49.75in.	844 lbs.	724 lbs.
HEO-2004-0E9G	2000	4.2	6.0/208V, 3Ø, 20.1A	386,400	56.5in.x29in.x49.75in.	844 lbs.	724 lbs.

Model No.	PSI	GPM	HP/Motor	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HEO-3004-0E2G	3000	3.9	8.0/230V, 1Ø, 38.6A	393,000	56.5in.x29in.x49.75in.	878 lbs.	758 lbs.
HEO-3004-0E3G	3000	3.9	8.0/230V, 3Ø, 21.6A	393,000	56.5in.x29in.x49.75in.	878 lbs.	758 lbs.
HEO-3004-0E4G	3000	3.9	8.0/460V, 3Ø, 10.8A	393,000	56.5in.x29in.x49.75in.	878 lbs.	758 lbs.
HEO-3004-0E8G	3000	3.9	8.0/208V, 1Ø, 42.1A	393,000	56.5in.x29in.x49.75in.	878 lbs.	758 lbs.
HEO-3004-0E9G	3000	3.9	8.0/208V, 3Ø, 24.6A	393,000	56.5in.x29in.x49.75in.	878 lbs.	758 lbs.

Model No.	PSI	GPM	HP/Motor	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HEO-3005-0E2G	3000	4.8	10.0/230V, 1Ø, 45.6A	428,400	56.5in.x29in.x49.75in.	878 lbs.	758 lbs.
HEO-3005-0E3G	3000	4.8	10.0/230V, 3Ø, 26.6A	428,400	56.5in.x29in.x49.75in.	878 lbs.	758 lbs.
HEO-3005-0E4G	3000	4.8	10.0/460V, 3Ø, 13.3A	428,400	56.5in.x29in.x49.75in.	878 lbs.	758 lbs.
HEO-3005-0E8G	3000	4.8	10.0/208V, 1Ø, 50.3A	428,400	56.5in.x29in.x49.75in.	878 lbs.	758 lbs.
HEO-3005-0E9G	3000	4.8	10.0/208V, 3Ø, 30.6A	428,400	56.5in.x29in.x49.75in.	878 lbs.	758 lbs.

### Options (Consult price list for qualifying models)

HX-0104, HX-0112

**K7 unloader (flow activated) (auto start/stop N/A)** - Converts pressure trapping unloader system to flow actuated K7 unloader. Pressure is not trapped in the discharge line when trigger is released

HX-0106

**Hour meter** - Displays number of hours unit has been in operation

HX-0107 \*

**Time delay shutdown** - Timer will shut unit off automatically when trigger gun is released and timer reaches setting

HX-0108 \*

**(1) Remote station (auto start/stop N/A)** - Adds control box which may be mounted away from unit to control on/off, burner and soap injection

HX-0223 \*

**Time delay shutdown and first remote box (kit option)** - Timer will shut unit off automatically when trigger gun is released and timer reaches setting; adds control box which may be mounted away from unit to control on/off, burner and soap injection

HX-0110

**Additional remotes (up to 3)** - Additional remotes that may be added to unit after the first remote is installed

HX-0111

**Auto start/stop** - When trigger gun is released timer will turn unit off, when trigger gun is pulled unit will restart

HX-0113, HX-0114

**Dual gun control** - Two guns may be operated at the same time. Flow is divided between the two guns while each operator maintains equal system pressure

HX-0115

**Stainless-steel access panel** - Converts powder coated painted access panels to stainless-steel material

HX-0116

**Stainless-steel coil wrap** - Converts powder coated painted coil wrap to stainless-steel material

HX-0117

**Painted box kit option** - Converts side panels to painted material

HX-0118

**Painted and stainless-steel box kit option** - Converts side panels to stainless-steel material

HX-0119 - HX-0122

**250°F steam upgrade** - Steam option adjusts unloader valve counter-clockwise increasing outlet temperature to 250°F while lowering system pressure

HX-0124

**Auto start/stop and first remote option** - Auto start/stop option - when trigger gun is released timer will turn unit off, when trigger gun is pulled unit will restart; adds control box which may be mounted away from unit to control on/off, burner and soap injection

HX-0218

**(2) 10-gallon fuel tanks** - Adds 20-gallon fuel capacity to unit versus hose hook-up to fuel supply

\* Options HX-0107 & HX-0108 cannot be ordered together, you will need to order HX-0223 instead.

Distributed by:

# ClearBlu

ENVIRONMENTAL

## Hot Water Pressure Washers HEO Series



# HEO Series

Designed, manufactured and tested in the tradition of quality. This stationary diesel powered hot water is a perfect choice for an efficient wash bay set-up.

DIESEL - BELT DRIVE

STATIONARY

## Additional Features:

- ✓ Open drip-proof electric motor with thermal overload protection
- ✓ Factory preset trapping unloader
- ✓ Thermal relief valve
- ✓ Pressure switch and over-pressure safety controls
- ✓ 24-volt control system
- ✓ Polyethylene float tank (4-gallon with in-line screen filter)
- ✓ Temperature rise 150°F/66°C above ambient; achieves 250°F/121°C outlet temperature with steam option
- ✓ Quick connect nozzles (0°, 15°, 25° and 40°)
- ✓ Powder coated stainless-steel side panels and frame




Control panel shown with On/Off burner switch, On/Off pump/motor switch, and adjustable thermostat



Beckett burner with fuel/water separator



10-inch draft diverter included (21-inch height)



General belt drive triplex ceramic plunger pump has the best warranty in the industry

