


HEG HV Specifications

Model No.	PSI	GPM	HP/Motor	BTU per hour		Dimensions (LxWxH)	Ship Wt.	Net Wt.
				Natural Gas	LP Gas (vapor only)			
HEG-2010-0E3G	2000	9.9	15.0/230V, 3Ø, 39.0A	768,000	730,000	78.5in.x34.75in.x65.75in.	1570 lbs.	1420 lbs.
HEG-2010-0E4G	2000	9.9	15.0/460V, 3Ø, 19.2A	768,000	730,000	78.5in.x34.75in.x65.75in.	1570 lbs.	1420 lbs.
HEG-2010-0E5G	2000	9.9	15.0/575V, 3Ø, 15.4A	768,000	730,000	78.5in.x34.75in.x65.75in.	1539 lbs.	1389 lbs.
HEG-2010-0E9G	2000	9.9	15.0/208V, 3Ø, 42.5A	768,000	730,000	78.5in.x34.75in.x65.75in.	1553 lbs.	1403 lbs.

Model No.	PSI	GPM	HP/Motor	BTU per hour		Dimensions (LxWxH)	Ship Wt.	Net Wt.
				Natural Gas	LP Gas (vapor only)			
HEG-3008-0E3G	3000	7.8	15.0/230V, 3Ø, 39.0A	650,000	619,500	70in.x34.75in.x54.5in.	1207 lbs.	1057 lbs.
HEG-3008-0E4G	3000	7.8	15.0/460V, 3Ø, 19.2A	650,000	619,500	70in.x34.75in.x54.5in.	1207 lbs.	1057 lbs.
HEG-3008-0E5G	3000	7.8	15.0/575V, 3Ø, 15.4A	650,000	619,500	70in.x34.75in.x54.5in.	1176 lbs.	1026 lbs.
HEG-3008-0E9G	3000	7.8	15.0/208V, 3Ø, 42.5A	650,000	619,500	70in.x34.75in.x54.5in.	1190 lbs.	1040 lbs.

Options

- HX-0180, HX-0189** **Liquid propane** - Converts natural gas pressure washer to operate on liquid propane (vapor only)
- HX-0181** **Auto start/stop** - When trigger gun is released timer will turn unit off, when trigger gun is pulled unit will restart
- HX-0182** **(1) Remote station** - Adds control box which may be mounted away from unit to control on/off, burner and soap injection
- HX-0183** **Additional remotes (up to 3)** - Additional remotes that may be added to unit after the first remote is installed
- HX-0185, HX-0191** **Dual gun control** - Two guns may be operated at the same time. Flow is divided between the two guns while each operator maintains equal system pressure, **includes modulating thermostat**
- HX-0186, HX-0192** **Modulating thermostat** - Regulating gas valve prevents drastic temperature swings by regulating gas flow at operating temperatures
- HX-0187, HX-0193** **Stainless-steel access panels** - Converts powder coated paint access panels to stainless-steel material
- HX-0188, HX-0194** **Stainless-steel coil wrap** - Converts powder coated paint coil wrap to stainless-steel material



Optional modulating thermostat available (HX-0186 or HX-0192)

Model #	HX-0180	HX-0181	HX-0182	HX-0183	HX-0185	HX-0186	HX-0187	HX-0188	HX-0189	HX-0191	HX-0192	HX-0193	HX-0194
HEG-2010		●	●	●		●			●	●	●	●	●
HEG-3008	●	●	●	●	●	●	●	●	●	●	●	●	●

ClearBlu

ENVIRONMENTAL

Hot Water Pressure Washers HEG HV Series



Distributed by:



HEG HV Series

All the same great features you come to expect from us, but with the high volume wash and natural gas/LP features built-in. This is an excellent choice for heavy mud and solids removal application.

HIGH VOLUME NATURAL GAS/LP - BELT DRIVE


STATIONARY



Belt drive triplex ceramic plunger General Pump has the best warranty in the industry



Easy-to-access control panel



Polyethylene float tank (8-gallon with in-line screen filter) prevents rusting



12-inch draft diverter included (24-inch height)



HEG-3008-0E4G shown with panels off

Additional Features:

- ✓ Open drip-proof electric motor with thermal overload protection
- ✓ Natural gas or LP gas-fired (vapor only) natural draft with aspirating-type burner, 12-inch stack
- ✓ Factory preset trapping unloader
- ✓ Thermal relief valve
- ✓ Pressure switch and over-pressure safety controls
- ✓ 24-volt control system
- ✓ Electronic ignition with standing pilot light
- ✓ 3/4-schedule 80-coil with 8 pancake heat exchanger (HEG-2010 models)
- ✓ Hour meter
- ✓ Time delay shutdown will automatically shut unit off when trigger is released and timer reaches setting
- ✓ Temperature rise 150°F/66°C above ambient
- ✓ Quick connect nozzles (0°, 15°, 25° and 40°)

NATURAL GAS INSTALLATION RECOMMENDATION:

Mi-T-M's natural gas pressure washer must have a clearance of 2-feet on all sides of the unit and 4-feet above the unit.

Gas Supply Line

Natural Gas

7- to 8-inch water column input

LP Gas

12- to 14-inch water column input

Recommended Pipe Sizes for Gas Supply Line

Natural Gas

Distance to Unit From Regulator	Pipe Size
0- to 50-feet	1½-inch 1PS
50- to 100-feet	2-inch 1PS
100- to 200-feet	2½-inch 1PS

LP Gas

Distance to Unit From Regulator	Pipe Size
0- to 50-feet	1-inch 1PS
50- to 100-feet	1½-inch 1PS
100- to 200-feet	1¾-inch 1PS

